

REMARKS

The Office Action dated July 15, 2003, has been received and carefully considered. In this response, claims 6, 10, 14-18, 21, 24-26, 28, 29, and 39 have been amended. Entry of the amendments to the claims 6, 10, 14-18, 21, 24-26, 28, 29, and 39 is respectfully requested. Reconsideration of the outstanding rejections in the present application is also respectfully requested based on the following remarks.

I. THE INDEFINITENESS REJECTION OF CLAIMS 10-16

On page 2 of the Office Action, claims 10-16 were rejected under 35 U.S.C. § 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the invention. This rejection is hereby respectfully traversed with amendment.

The Examiner asserts that that claims 10 and 16 contain terms lacking antecedent basis. Claims 10 and 14-16 have been amended to address the concerns of the Examiner.

In view of the foregoing, it is respectfully requested that the aforementioned indefiniteness rejection of claims 10-16 be withdrawn.

II. THE ANTICIPATION REJECTION OF CLAIMS 1-9, 17-23, AND 33-39

On pages 2-4 of the Office Action, claims 1-9, 17-23, and 33-39 were rejected under 35 U.S.C. § 102(b) as being anticipated by Coyle et al. (U.S. Patent No. 5,003,463). This rejection is hereby respectfully traversed.

Under 35 U.S.C. § 102, the Patent Office bears the burden of presenting at least a prima facie case of anticipation. In re Sun, 31 USPQ2d 1451, 1453 (Fed. Cir. 1993) (unpublished). Anticipation requires that a prior art reference disclose, either expressly or under the principles of inherency, each and every element of the claimed invention. Id.. "In addition, the prior art reference must be enabling." Akzo N.V. v. U.S. International Trade Commission, 808 F.2d 1471, 1479, 1 USPQ2d 1241, 1245 (Fed. Cir. 1986), cert. denied, 482 U.S. 909 (1987). That is, the prior art reference must sufficiently describe the claimed invention so as to have placed the public in possession of it. In re Donohue, 766 F.2d 531, 533, 226 USPQ 619, 621 (Fed. Cir. 1985). "Such possession is effected if one of ordinary skill in the art could have combined the publication's description of the invention with his own knowledge to make the claimed invention." Id..

The Examiner asserts that Coyle et al. teach the present invention as claimed. However, the Examiner fails to explain

how Coyle et al. teach, or even suggest, how first data is transmitted from a first device to a second device and second data is transmitted from the second device to the first device, all simultaneously over a common bus. This feature is prevalent in claims 1-9, 17-23, and 33-39 of the present application and is supported throughout the specification. It is respectfully submitted that Coyle et al. fail to teach, or even suggest, such a feature. Accordingly, it is respectfully submitted that the present invention is not anticipated by Coyle et al..

At this point it should be noted that claims 6, 17, 18, 21, and 39 have been amended to clarify that the above-discussed feature is indeed prevalent in claims 6, 17, 18, 21, and 39.

In view of the foregoing, it is respectfully submitted that the aforementioned anticipation rejection of claims 1-9, 17-23, and 33-39 is improper, and the withdrawal of such rejection is respectfully requested.

III. THE ANTICIPATION REJECTION OF CLAIMS 10-16 AND 24-32

On pages 4-5 of the Office Action, claims 10-16 and 24-32 were rejected under 35 U.S.C. § 102(e) as being anticipated by Tamura et al. (U.S. Patent No. 6,493,394). This rejection is hereby respectfully traversed.

The Examiner asserts that Tamura et al. teach the present invention as claimed. However, the Examiner fails to explain how Tamura et al. teach, or even suggest, simultaneous bidirectional signaling on a common bus in any manner. This features is prevalent in claims 10-16 and 24-32 of the present application and is supported throughout the specification. It is respectfully submitted that Tamura et al. fail to teach, or even suggest, such a feature. In fact, Tamura et al. teach away from such a feature by indicating that the conditions associated with such a feature would result only from an error (see column 41, lines 11-16). Accordingly, it is respectfully submitted that the present invention is not anticipated by Tamura et al..

At this point it should be noted that claims 10, 14-16, 24-26, 28, and 29 have been amended to clarify that the above-discussed feature is indeed prevalent in claims 10, 14-16, 24-26, 28, and 29.

In view of the foregoing, it is respectfully submitted that the aforementioned anticipation rejection of claims 10-16 and 24-32 is improper, and the withdrawal of such rejection is respectfully requested.

IV. CONCLUSION

In view of the foregoing, it is respectfully submitted that the present application is in condition for allowance, and an early indication of the same is courteously solicited. The Examiner is respectfully requested to contact the undersigned by telephone at the below listed telephone number, in order to expedite resolution of any issues and to expedite passage of the present application to issue, if any comments, questions, or suggestions arise in connection with the present application.

To the extent necessary, a petition for an extension of time under 37 CFR § 1.136 is hereby made.

Please charge any shortage in fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account No. 50-0206, and please credit any excess fees to the same deposit account.

Respectfully submitted,

Hunton & Williams LLP

By: 

Thomas E. Anderson

Registration No. 37,063

TEA/vrp

Hunton & Williams LLP
1900 K Street, N.W.
Washington, D.C. 20006-1109
Telephone: (202) 955-1500
Facsimile: (202) 778-2201
Date: October 15, 2003

APPENDIX A

1. (Original) A method for providing simultaneous bidirectional signaling in a bus topology comprising the steps of:

selecting a first device and a second device from among a plurality of devices operably coupled to a common bus to exchange a first set of data;

scheduling a first exchange slot over which the first device and the second device are to exchange the first set of data; and

during the first exchange slot, simultaneously transmitting a first portion of the first set of data from the first device to the second device over the common bus and transmitting a second portion of the first set of the data from the second device to the first device over the common bus.

2. (Original) The method of claim 1 further comprising the steps of:

selecting the first device and a third device to exchange a second set of data;

scheduling a second exchange slot over which the first device and the third device are to exchange the second set of data; and

during the second exchange slot, simultaneously

transmitting a first portion of the second set of data from the first device to the third device over the common bus and transmitting a second portion of the second set of the data from the third device to the first device over the common bus.

3. (Original) The method of claim 2 further comprising the step of:

introducing a turnaround delay between the first exchange slot and the second exchange slot.

4. (Original) The method of claim 3 wherein the turnaround delay is less than twice an end-to-end propagation delay of the common bus.

5. (Original) The method of claim 1 wherein the first device is a memory controller, and the second device is a memory device and wherein the first portion of the first set of data and the first portion of the second set of data are write data and the second portion of the first set of data and the second portion of the second set of data are read data.

6. (Currently Amended) A system providing simultaneous bidirectional signaling using a bus topology, the system

comprising:

a first device operably coupled to a bus;

a second device operably coupled to the bus, the first device transmitting a first portion of a first set of data over the bus to the second device and the second device transmitting a second portion of the first set of data over the bus to the first device simultaneously during a first exchange slot; and

a third device operably coupled to the bus, the first device transmitting a first portion of a second set of data over the bus to the third device and the third device transmitting a second portion of the second set of data over the bus to the first device simultaneously during a second exchange slot.

7. (Original) The system of claim 6 wherein a turnaround delay exists between the first exchange slot and the second exchange slot.

8. (Original) The system of claim 7 wherein the turnaround delay is less than twice an end-to-end propagation delay of the bus.

9. (Original) The system of claim 6 wherein the first device is a memory controller, and the second device is a memory device

and wherein the first portion of the first set of data and the first portion of the second set of data are write data and the second portion of the first set of data and the second portion of the second set of data are read data.

10. (Currently Amended) A device coupled to a bus in a bus topology ~~capable of~~ for providing simultaneous bidirectional signaling, the device comprising:

Q1 a driver ~~capable of~~ configured to provide additive signaling, ~~said~~ the driver ~~circuit~~ applying transmit signals to the bus;

a receiver circuit operably coupled to the driver, the receiver circuit ~~capable of~~ configured to effectively subtracting the transmit signals to receive received signals from the bus, the driver and the receiver circuit operating during an exchange slot.

11. (Original) The device of claim 10 wherein the device is coupled to the bus by an impedance-matching splitter.

12. (Original) The device of claim 10 wherein the device further comprises:

a terminator operably coupled to the driver and the

receiver circuit, the terminator providing a controlled termination impedance.

13. (Original) The device of claim 10 wherein the device further comprises:

a transmit circuit operably coupled to the driver, the transmit circuit comprising a transmit buffer, the transmit buffer holding data pending arrival of the exchange slot.

14. (Currently Amended) The device of claim 13 wherein the transmit buffer further comprises:

a plurality of transmit buffers, the plurality of transmit buffers ~~adaptable~~ configured to hold data destined for different other devices.

15. (Currently Amended) The device of claim 13 wherein the receiver circuit further comprises:

a comparator operably coupled to the transmitter and to the driver, the comparator ~~adaptable~~ configured to effectively subtract the transmit signals to yield received signals from the bus; and

a receiver operably coupled to the comparator, the receiver receiving the received signals and obtaining received data from

the received signals.

16. (Currently Amended) The device of claim 15 further comprising:

an enabling circuit responsive to an exchange slot indication, the enabling circuit enabling the operation of the transmit circuit and the receive circuit during the exchange slot.

17. (Currently Amended) A memory system comprising:

a memory controller;

a bus operably coupled to the memory controller;

a first memory device operably coupled to the bus, the first memory device ~~adapted~~ configured to simultaneously send first read data to the memory controller via the bus and receive first write data from the memory controller via the bus; and

a second memory device operably coupled to the ~~memory controller-bus~~, the second memory device ~~adapted~~ configured to simultaneously send second read data to the memory controller via the bus and receive second write data from the memory controller via the bus.

18. (Currently Amended) The memory system of claim 17 wherein

the first memory device is ~~adapted~~ configured to simultaneously send the first read data to the memory controller and receive the first write data from the memory controller during a first exchange slot and wherein the second memory device is ~~adapted~~ configured to simultaneously send the second read data to the memory controller and receive the second write data from the memory controller during a second exchange slot.

19. (Original) The memory system of claim 18 wherein the memory controller comprises:

a first write buffer to hold the first write data pending arrival of the first exchange slot.

20. (Original) The memory system of claim 19 wherein the memory controller comprises:

a second write buffer to hold the second write data pending arrival of the second exchange slot.

21. (Currently Amended) The memory system of claim 17 wherein the bus comprises:

a conductor operably coupling the first memory device and the second memory device to the memory controller, wherein the first memory device is ~~adapted~~ configured to simultaneously send

21
a first read bit of the first read data to the memory controller over the conductor and receive a first write bit of the first write data from the memory controller over the conductor during a first exchange slot and wherein the second memory device is ~~adapted~~ configured to simultaneously send a second read bit of the second read data to the memory controller over the conductor and receive a second write bit of the second write data from the memory controller over the conductor during a second exchange slot.

22. (Original) The memory system of claim 21 wherein a turnaround delay sufficient to prevent inter-symbol interference is introduced between the first exchange slot and the second exchange slot.

23. (Original) The memory system of claim 17 wherein the memory controller performs coherency checking during memory access operations.

24. (Currently Amended) A memory device ~~adaptable to be coupled to a bus~~ comprising:

a driver ~~adapted~~ configured to drive ~~the~~ a bus with read data during an exchange slot while write data are present on the

bus;

a receiver circuit operably coupled to the driver, the receiver circuit ~~capable of~~ configured to receive the write data from the bus during the exchange slot while the driver is driving the bus with the read data; and

a memory circuit operably coupled to the receiver circuit, the memory circuit ~~adapted~~ configured to provide the read data and to store the write data.

25. (Currently Amended) The memory device of claim 24 further comprising:

an enabling circuit responsive to an exchange slot indication, the enabling circuit operably coupled to the driver and the receiver circuit, the enabling circuit enabling interaction of the driver and the receiver circuit with the bus during the exchange slot.

26. (Currently Amended) The memory device of claim 25 wherein the enabling circuit is ~~adapted~~ configured to be responsive to the exchange slot indication following a turnaround delay sufficient to prevent inter-symbol interference.

27. (Original) The memory device of claim 24 further

comprising:

a transmit circuit operably coupled to the driver, the transmit circuit comprising a transmit buffer, the transmit buffer holding the read data pending arrival of the exchange slot.

28. (Currently Amended) A memory controller ~~adapted to be coupled to a bus~~ comprising:

a driver ~~adapted~~ configured to drive ~~the~~ a bus with first write data destined for a first memory device during a first exchange slot while first read data from the first memory device are present on the bus;

a receiver circuit operably coupled to the driver, the receiver circuit ~~adapted~~ configured to receive the first read data from the bus during the first exchange slot while the driver is driving the bus with the first write data.

29. (Currently Amended) The memory controller of claim 28 wherein the driver is further ~~adapted~~ configured to drive the bus with second write data destined for a second memory drive during a second exchange slot while second read data from the second memory device are present on the bus and wherein the receiver circuit is further ~~adapted~~ configured to receive the

second read data from the bus during the second exchange slot while the driver is driving the bus with the second write data.

30. (Original) The memory controller of claim 29 wherein a turnaround delay sufficient to prevent inter-symbol interference is introduced between the first exchange slot and the second exchange slot.

31. (Original) The memory controller of claim 28 further comprising:

a transmit circuit operably coupled to the driver to transmit the first write data and the second write data to the driver, the transmit circuit comprising a transmit buffer to hold the first write data pending arrival of the first exchange slot and the second write data pending arrival of the second exchange slot.

32. (Original) The memory controller of claim 31 wherein the transmit buffer comprises:

a first transmit buffer to hold the first write data pending arrival of the first exchange slot; and

a second memory buffer to hold the second write data pending arrival of the second exchange slot.

33. (Original) A method for providing simultaneous bidirectional communication between a memory controller and a plurality of memory devices comprising the steps of:

during a first exchange slot, simultaneously communicating over a common bus first write data from the memory controller to a first memory device of the plurality of memory devices and first read data from the first memory device to the memory controller; and

during a second exchange slot, simultaneously communicating over a common bus second write data from the memory controller to a second memory device of the plurality of memory devices and second read data from the second memory device to the memory controller.

34. (Original) The method of claim 33 further comprising the step of:

holding the first write data destined for the first memory device in the memory controller pending arrival of the first exchange slot.

35. (Original) The method of claim 34 further comprising the step of:

holding the second write data destined for the second memory device in the memory controller pending arrival of the second exchange slot.

36. (Original) The method of claim 35 wherein the step of holding the first write data occurs in a first write buffer and wherein the step of holding the second write data occurs in a second write buffer.

37. (Original) The method of claim 35 further comprising the steps of:

holding the first read data destined for the memory controller in the first memory device; and

holding the second read data destined for the memory controller in the second memory device.

38. (Original) The method of claim 37 wherein the step of simultaneously communicating over the common bus the first write data from the memory controller to the first memory device and the first read data from the first memory device to the memory controller occurs after a specified amount of the first write data destined for the first memory device is hold in the memory controller.

39. (Currently Amended) A system for bidirectional communication of data over a common bus comprising:

a first device operably coupled to the common bus, the first device comprising a first-to-second transmit buffer to hold first-to-second data and a first-to-third transmit buffer to hold first-to-third data;

R a second device operably coupled to the common bus, the second device comprising a second-to-first transmit buffer to hold second-to-first data;

a third device operably coupled to the common bus, the third device comprising a third-to-first transmit buffer to hold third-to-first data; and

a scheduler operably coupled to the common bus, the scheduler scheduling the first device to transmit the first-to-second data and the second device to transmit the second-to-first data over the common bus simultaneously during a first exchange slot and scheduling the first device to transmit the first-to-third data and the third device to transmit the third-to-first data over the common bus simultaneously during a second exchange slot, the scheduler introducing a turnaround delay sufficient to prevent inter-symbol interferences between the first exchange slot and the second exchange slot.